


SMV100 3-36 SAH

STANDARD EQUIPMENT



0.144.0108 HEPA (H14) + PTFE cartridge filter (3x)
0.144.0008 Quick release adaptor Ø60-50 (1x)
There isn't any hose or tool provided within the unit.

Optional minimum set to run the unit:

6.205.0049 3m complete EVA Ø50 hose set (1x)

Optional:

Longopack set

0.144.0110 Hopper for spool bag collection
0.144.0111 Tray for spool bag collection
0.144.0112 Longopack 22m bag spools (box of 4)

Filter

0.144.0109 ULPA (H13) D.O.P. cartridge filter

Equipped with:

- 3 silenced two stage by-pass cooling motors
- Power coated steel structure and containers
- Self-cleaning filter system for continuous operations
- 3 HEPA + PTFE cartridge conductive filters
- Metal side inlet channel and AISI 304 stainless steel filter protection
- Wheeled container with inbuilt quick release handle, drain plug and full load level
- Trolley with front pivoting non-marking wheels (with breake) & large inbuilt accessories basket
- Removable motors unit header through metal hooks

SMV100 3-36 SAH	
code	0.044.0301
abs. power W	3300
n°/type motor	3 x two stages universal
max vacuum (actual)	24 kPa (24kPa)
max Airflow	510 m³/h - 142 l/s
container capacity	100 l
noise level	78 dB(A)
voltage	230 V~50 Hz (1Ph)
inlet Ø - type (s=straight; t=tangential)	60 mm - t
filtering capacity/surface	1 µm - 99,995% (H Class)/ 9000 cm²
cable lenght	10 m
dimensions/weight	60x80x147 cm/59 kg - 130 lb