



HD 13/50 -4 Classic *CN





1 High-performance crankshaft pump

Reliable and durable Kärcher high-performance crankshaft pump ensures optimal pressure.

3 Reliable and durable

Longer service life, less maintenance effort and lower costs. Ideal for industrial use.

2 Dry run protection

Protects the pump against dry running.

TECHNICAL DATA AND EQUIPMENT



HD 13/50 -4 Classic *CN

		·				
Technical data						
Order no.		1.367-159.0				
EAN code		4054278242484				
Working pressure	bar / MPa	100-500 / 10-50				
Flow rate	l/h	500-1300				
Max. inlet temperature	°C	max. 60				
Drive		E-Motor 400 V / 50 Hz				
Motor rating	kW	22				
Weight	kg	275				
Dimensions (L × W × H) mm		1110 × 800 × 950				
Equipment						
Electro start		-				

Equipment		
Electro start		-
High-pressure hose	m	10 / Heavy duty
Spray gun		Industrial trigger gun
Stainless steel lance	mm	700
Flat jet nozzle		
Water filter		I
Safety valve		
Elapsed time counter		1

 \blacksquare Included in the scope of supply.

HD 13/50 -4 CLASSIC *CN 1.367-159.0











		Order no.	Length		Price	Description	
High-pressure hoses		ı		I.			
Pressure hose	1	6.391-848.0				650 bar, M 22 x 1.5	
	2	6.391-857.0				650 bar, M 22 x 1.5.	
Trigger guns	·						
Kärcher industry gun	3	4.775-824.0				650 bar – industrial spray gun with optimised flow. Robustness and durability for professional use. Food-safe and saltwater-resistant materials. Connector for HP hoses M 22 x 1.5.	
Spray lances			1	 I		X 10.	
Spray lance	4	4.760-679.0				With nozzle holder.	
	5	4.760-653.0					
	6	4.760-675.0					
	7	4.760-677.0					
Spray lance extension	8	4.760-699.0				Spray lance extension 800 mm, 65 MPa.	
Screw nozzles F21	·						
Dummy nozzle F21	9	6.025-237.0				F21 screw-on dummy nozzle. Suitable for working pressures of up to 3,000 bar.	

lacksquare Included in the scope of supply. \Box Available accessories.